

Ruby - Bug #3071

Convert rubygems and rdoc to use psych

04/01/2010 05:35 AM - tenderlovmaking (Aaron Patterson)

Status:	Rejected	Backport:
Priority:	Normal	
Assignee:	tenderlovmaking (Aaron Patterson)	
Target version:		
ruby -v:	ruby 1.9.2dev (2010-03-31 trunk 27130) [x86_64-darwin10.2.0]	
Description =begin Rubygems and rdoc should be converted to use psych. The attached patch converts them. =end		

History

#1 - 04/01/2010 06:44 AM - headius (Charles Nutter)

=begin

Doesn't this mean the the RubyGems codebase would now be forked between 1.8 and 1.9? And not work on any impls that don't have Psych yet?

On Wednesday, March 31, 2010, Aaron Patterson redmine@ruby-lang.org wrote:

Bug #3071: Convert rubygems and rdoc to use psych
<http://redmine.ruby-lang.org/issues/show/3071>

Author: Aaron Patterson
Status: Open, Priority: Normal
Assigned to: Eric Hodel
ruby -v: ruby 1.9.2dev (2010-03-31 trunk 27130) [x86_64-darwin10.2.0]

Rubygems and rdoc should be converted to use psych. The attached patch converts them.

<http://redmine.ruby-lang.org>

=end

#2 - 04/01/2010 07:10 AM - bitsweat (Jeremy Daer)

=begin

On Wed, Mar 31, 2010 at 2:43 PM, Charles Oliver Nutter
headius@headius.com wrote:

Doesn't this mean the the RubyGems codebase would now be forked between 1.8 and 1.9? And not work on any impls that don't have Psych yet?

The patch uses psych or yaml according to availability.

jeremy

=end

#3 - 04/01/2010 11:53 AM - nobu (Nobuyoshi Nakada)

- Status changed from Open to Rejected

- Assignee changed from drbrain (Eric Hodel) to tenderlovmaking (Aaron Patterson)

=begin

Psych must provide YAML compatible layer instead.

=end

#4 - 04/01/2010 02:44 PM - drbrain (Eric Hodel)

=begin

I don't understand, this patch seems to use a YAML compatible layer so it will work with both Psych and syck

=end

#5 - 04/01/2010 05:17 PM - nobu (Nobuyoshi Nakada)

=begin

Hi,

At Thu, 1 Apr 2010 14:21:56 +0900,
Aaron Patterson wrote in [\[ruby-core:29197\]](#):

Psych must provide YAML compatible layer instead.

I don't understand. Should I provide the YAML constant too?

And lib/yaml.rb should select Syck or Psych. If so, users can choose either, probably at configuration. It's a bad idea to let all libraries write such selection.

Rather I want move lib/yaml to ext/syck/lib, and incorporate your yamler into lib/yaml.rb. Also, ext/{syck,psych} should go to below of ext/yaml, I think.

--

Nobu Nakada

=end

#6 - 04/05/2010 01:38 PM - naruse (Yui NARUSE)

=begin

NOTE: Ruby::Specification#to_yaml uses deprecated API: YAML.quick_emit.

=end

Files

rgems.patch	17.2 KB	04/01/2010	tenderlovemaking (Aaron Patterson)
-------------	---------	------------	------------------------------------