

Ruby - Bug #5845

Addrinfo#connect_from Addrinfo

01/05/2012 06:35 PM - ohai (Ippei Obayashi)

Status:	Closed	
Priority:	Normal	
Assignee:		
Target version:		
ruby -v:	ruby 2.0.0dev (2012-01-04 trunk 34210) [x86_64-linux]	Backport:

Description

Addrinfo#connect_from (ext/socket/lib/socket.rb) rdoc

Addrinfo object can be taken for the argument.

Addrinfo.tcp("www.ruby-lang.org",
80).connect_from(Addrinfo.tcp("0.0.0.0", 4649)) {|s|

s.print "GET / HTTP/1.0\r\nHost: www.ruby-lang.org\r\n\r\n"

puts s.read

}

```
require 'socket'
Addrinfo.tcp("www.example.com", 80).connect_from(Addrinfo.tcp("0.0.0.0", 49021)) {|s|
  p s.local_address.ip_port
  s.close
}
Addrinfo#family_addrinfo  Addrinfo  
```

Associated revisions

Revision 268d1a22 - 01/09/2012 11:11 AM - akr (Akira Tanaka)

- ext/socket/lib/socket.rb (family_addrinfo): return the given addrinfo object.
Patch by Ippei Obayashi. [ruby-dev:45095] [Bug #5845]

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/trunk@34244 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

History

#1 - 01/09/2012 08:11 PM - akr (Akira Tanaka)

- Status changed from Open to Closed
- % Done changed from 0 to 100

This issue was solved with changeset r34244.
Ippei, thank you for reporting this issue.
Your contribution to Ruby is greatly appreciated.
May Ruby be with you.

-
- ext/socket/lib/socket.rb (family_addrinfo): return the given
addrinfo object.
Patch by Ippei Obayashi. [\[ruby-dev:45095\]](#) [Bug [#5845](#)]

Files

addrinfo_family_addrinfo_fix.patch	722 Bytes	01/05/2012	ohai (Ippei Obayashi)
addrinfo_connect_from_test.patch	836 Bytes	01/05/2012	ohai (Ippei Obayashi)