

Ruby - Feature #6626

Readline.delete_text

06/22/2012 03:20 PM - nobu (Nobuyoshi Nakada)

Status:	Closed	
Priority:	Normal	
Assignee:	kouji (Kouji Takao)	
Target version:	2.6	
Description		
<pre>=begin [Feature #5785] insert_text line_buffer delete_text line_buffer test_readline.rb ((<PR#132 URL:https://github.com/ruby/ruby/pull/132>)) --- Readline.delete_text(start=0[, length]) -> self start length length start --- Readline.delete_text(start..end) -> self start end =end</pre>		

Associated revisions

Revision 56af74277c5a3fd9dc5f07524248f78a292b280e - 07/22/2013 12:37 AM - kouji (Kouji Takao)

- ext/readline/readline.c (Init_readline): added
Readline.delete_text. [ruby-dev:45789] [Feature #6626]
 - ext/readline/extconf.rb: check for rl_delete_text() in Readline library.
- Thanks, Nobuyoshi Nakada, for the patch.

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/trunk@42101 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

Revision 56af7427 - 07/22/2013 12:37 AM - kouji (Kouji Takao)

- ext/readline/readline.c (Init_readline): added
Readline.delete_text. [ruby-dev:45789] [Feature #6626]
 - ext/readline/extconf.rb: check for rl_delete_text() in Readline library.
- Thanks, Nobuyoshi Nakada, for the patch.

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/trunk@42101 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

Revision 182cf90d30f1319f094adcf4c37ea8921c348453 - 07/23/2013 06:00 PM - naruse (Yui NARUSE)

fix test of r42101 [Feature #6626]

rl_delete_text removes characters in line_buffer, but it doesn't move rl_point.
Therefore it may cause invalid rl_point.

On following case, test_input_metachar causes test_insert_text failure.
(test_input_metachar_multibyte) is skipped because of locale
<http://c5664.rubyci.org/~chkbuild/ruby-trunk/log/20130723T133302Z.log.html.gz>

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/trunk@42146 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

fix test of r42101 [Feature #6626]

rl_delete_text removes characters in line_buffer, but it doesn't move rl_point.
Therefore it may cause invalid rl_point.

On following case, test_input_metachar causes test_insert_text failure.
(test_input_metachar_multibyte) is skipped because of locale
<http://c5664.rubyci.org/~chkbuild/ruby-trunk/log/20130723T133302Z.log.html.gz>

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/trunk@42146 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

History

#1 - 02/01/2013 02:46 PM - shugo (Shugo Maeda)

- Tracker changed from Bug to Feature

#2 - 02/01/2013 02:47 PM - shugo (Shugo Maeda)

- Target version changed from 2.0.0 to 2.6

feature request~~~~~next minor~~~~~

#3 - 07/10/2013 06:33 AM - kouji (Kouji Takao)

~~~~~

~~~~~(Mac OS X 10.7, GNU Readline 6.2)~~~~~  
~~~~~Mac OS~~~~~EditLine(libedit)~~~~~commit~~~~~  
~~~~~string.c~~~~~rb\_str\_subpos~~~~~rb\_str\_subpos~~~~~ext/re  
adline/readline.c~~~~~rb_str_subpos~~~~~rb_str_subpos~~~~~...

~~~~~rb\_str\_subpos~~~~~  
~~~~~Readline~~~~~Readline~~~~~rb\_str\_subpos~~~~~rb\_str\_subpos~~~~~  
~~~~~Readline~~~~~

#4 - 07/22/2013 09:37 AM - kouji (Kouji Takao)

- Status changed from Assigned to Closed  
- % Done changed from 0 to 100

This issue was solved with changeset r42101.  
Nobuyoshi, thank you for reporting this issue.  
Your contribution to Ruby is greatly appreciated.  
May Ruby be with you.

- ext/readline/readline.c (Init\_readline): added  
Readline.delete\_text. [\[ruby-dev:45789\]](#) [Feature #6626]
- ext/readline/extconf.rb: check for rl\_delete\_text() in Readline library.

Thanks, Nobuyoshi Nakada, for the patch.

Files

|                                                           |         |            |                         |
|-----------------------------------------------------------|---------|------------|-------------------------|
| 0001-string.c-rb_str_subpos.patch                         | 1.09 KB | 06/22/2012 | nobu (Nobuyoshi Nakada) |
| 0002-ext-readline-readline.c-Readline.delete_text.patch   | 4.32 KB | 06/22/2012 | nobu (Nobuyoshi Nakada) |
| 0003-test-readline-test_readline.rb-use-delete_text.patch | 1.2 KB  | 06/22/2012 | nobu (Nobuyoshi Nakada) |