

Ruby - Bug #12841

Kernel#exec(cmdname, arg1, ...) passes arg1 that is encoded strangely on Japanese Windows

10/14/2016 01:06 PM - dogatana (Toshihiko Ichida)

Status:	Closed	
Priority:	Normal	
Assignee:		
Target version:		
ruby -v:	ruby 2.3.0p0 (2015-12-25 revision 53290) [i386-mingw32]	Backport: 2.1: UNKNOWN, 2.2: UNKNOWN, 2.3: UNKNOWN

Description

Kernel#exec(cmdname, arg1, ...) の arg1 が Windows-31J でエンコードされている

Kernel#exec(cmdline) の cmdline が Windows-31J でエンコードされている

```
> ruby test.rb 
arg: , enc: Windows-31J, bytes: 82-a0

cmdline 

```

```
> irb
irb(main):001:0> Kernel.exec 'ruby test.rb '
arg: , enc: Windows-31J, bytes: 82-a0

cmdname, arg1  arg1

```

```
> irb
irb(main):001:0> Kernel.exec 'ruby', 'test.rb', ''
arg: , enc: Windows-31J, bytes: e3-81-81-45

bundler  Kernel#exec(cmdname, arg1, ...)

```

```
bundle exec mygemprogram 

```

gem のインストール時にエラーが発生する

Associated revisions

Revision 5d4309d068f731a17be791b0dfe6e484a39c25c8 - 10/14/2016 03:54 PM - nobu (Nobuyoshi Nakada)

process.c: use uaspawn

- process.c (proc_exec_cmd): use UTF-8 version aspawn. [ruby-dev:49838] [Bug #12841]

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/trunk@56424 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

Revision 5d4309d0 - 10/14/2016 03:54 PM - nobu (Nobuyoshi Nakada)

process.c: use uaspawn

- process.c (proc_exec_cmd): use UTF-8 version aspawn. [ruby-dev:49838] [Bug #12841]

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/trunk@56424 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

History

#1 - 10/14/2016 03:54 PM - nobu (Nobuyoshi Nakada)

- Status changed from Open to Closed

Applied in changeset r56424.

process.c: use uaspawn

- process.c (proc_exec_cmd): use UTF-8 version aspawn.
[\[ruby-dev:49838\]](#) [Bug [#12841](#)]

Files

test.rb	111 Bytes	10/14/2016	dogatana (Toshihiko Ichida)
---------	-----------	------------	-----------------------------