# Ruby - Feature #4672

# [PATCH] openssl: enable SSL\_MODE\_RELEASE\_BUFFERS if available

05/12/2011 04:05 PM - normalperson (Eric Wong)

Status: Closed
Priority: Normal

Assignee: MartinBosslet (Martin Bosslet)

Target version: 2.0.0

### Description

Available in OpenSSL 1.0.0a and later, this can save up to 34KB per idle connection.

Using the test script below run with the time(1) command on 64-bit Linux (needs /proc/\$PID/status to grab VmRSS:)

# before

conn\_clients: 500 srv\_clients: 500 VmRSS: 65428 kB

19.18user 1.86system 0:20.72elapsed 101%CPU (0avgtext+0avgdata 263952maxresident

0inputs+0outputs (0major+56932minor)pagefaults 0swaps

## after

conn\_clients: 500 srv\_clients: 500 VmRSS: 19228 kB

19.41user 1.53system 0:20.64elapsed 101%CPU (0avgtext+0avgdata 77424maxresident)

0inputs+0outputs (0major+20845minor)pagefaults 0swaps

(test script attached)

You can also pull my change via git:

git clone git://bogomips.org/ruby.git ssl-memory

# **Associated revisions**

#### Revision 41c517d1 - 06/22/2011 06:04 AM - MartinBosslet (Martin Bosslet)

 ext/openssl/ossl\_ssl.c: Use SSL\_MODE\_RELEASE\_BUFFERS if available. Thanks, Eric Wong, for providing the patch.
 [ Ruby 1.9 - Feature #4672 ] [ruby-core:36127]

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/trunk@32198 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

#### History

### #1 - 06/09/2011 06:32 AM - MartinBosslet (Martin Bosslet)

- Assignee set to nahi (Hiroshi Nakamura)

This patch seems reasonable. I looked at the implementation in OpenSSL (1.0.0d) and it looks like using SSL\_MODE\_RELEASE\_BUFFERS should not cause any problems.

Hiroshi, what do you think?

Regards, Martin

(PS: If you agree that we should apply this, please feel free to assign back to me for application of this patch)

06/15/2025 1/2

## #2 - 06/20/2011 07:45 PM - nahi (Hiroshi Nakamura)

- Status changed from Open to Assigned
- Assignee changed from nahi (Hiroshi Nakamura) to MartinBosslet (Martin Bosslet)

Excellent result. It looks like a gift from Tor project. There's no reason I can imagine not to apply this. Please apply this.

I think it's OK to commit this w/o writing a test. :)

# #3 - 06/22/2011 03:04 PM - Anonymous

- Status changed from Assigned to Closed
- % Done changed from 0 to 100

This issue was solved with changeset r32198. Eric, thank you for reporting this issue. Your contribution to Ruby is greatly appreciated. May Ruby be with you.

 ext/openssl/ossl\_ssl.c: Use SSL\_MODE\_RELEASE\_BUFFERS if available. Thanks, Eric Wong, for providing the patch.
 [ Ruby 1.9 - Feature #4672 ] [ruby-core:36127]

## **Files**

0001-openssl-enable-SSL_MODE_RELEASE_BUFFERS-if-available.patchKB		05/12/2011	normalperson (Eric Wong)
openssl_memory.rb	1.1 KB	05/12/2011	normalperson (Eric Wong)

06/15/2025